

IS 2180-5 weiss

neva
lux

Product code **4007841605018**

- UV-resistant plastic
- Including corner wall mount

neva
lux

120 x 78 x 55 mm



IS 2180-5 weiss

Product code **4007841605018**

Technical Data

IDENTIFICATION					
Variant	white	Segment-by-segment masking	Yes	Base light function	No
Version	Motion detectors	Electronic scalability	No	With remote control	No
DIMENSIONS		Mechanical scalability	No	Twilight setting teach	No
Dimensions L x W x H	120 x 78 x 55 mm	Tangential range	r = 8 m (101 m²) / r = 20 m (628 m²)	HOUSING & MATERIAL	
ELECTRICAL		Switching zones	504 switching zones	Protection class (IP)	IP54
Mains connection	230 – 240 V , 50 / 50 Hz	Optimal mounting height	2 m	Ambient temperature	-20 – 50 °C
Switching output 1 resistive	1000 W	CONNECTIVITY		Mounting location	corner wall
SENSOR TECHNOLOGY		Networking	Yes	Application location	Outdoors
Sensor technology	passive infrared	LIGHTING TECHNOLOGY		Mounting type	Surface wiring
Detection angle	180 °	Constant light regulation	No	Material	Plastic
Opening angle	90 °	SETTINGS		Colour	white
Sneak-under protection	Yes	Twilight setting	2 – 2000 lx	RAL colour	9010
		Time setting	5 sec – 15 min	SCOPE OF DELIVERY & WARRANTY	
				Manufacturer warranty	5 years

IS 2180-5 weiss

Product code **4007841605018**

Illustrations

MOUNTING HEIGHT



IS 2180-5 weiss

Product code **4007841605018**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841605018
Typ	IS 2180-5 weiss
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	