

XLED PRO Wide eNet - schwarz



Product code **4007841010249**

- Including STEINEL LED system
- Intelligent LED cooling system
- Optional basic lighting level
- UV resistant material
- Wireless interconnection
- Remote control RC9 included
- Smart Remote remote control optional

neva
lux

126 x 265 x 188 mm



XLED PRO Wide eNet - schwarz

Product code 4007841010249

Technical Data

IDENTIFICATION		Segment-by-segment masking		Yes		LIFETIME	
Variant	eNet - black	Tangential range		r = 12 m (302 m²)		LED lifetime max. °C	50000 h
DIMENSIONS		CONNECTIVITY				SETTINGS	
Dimensions L x W x H	126 x 265 x 188 mm	Networking		Yes		Twilight switch	Yes
ELECTRICAL		LIGHTING TECHNOLOGY				Twilight setting	2 – 1000 lx
Mains connection	220 – 240 V , 50 / 60 Hz	Colour temperature		4000 K		HOUSING & MATERIAL	
Power	24,8 W	LED colour deviation		SDCM3		Impact resistance	IK03
SENSOR TECHNOLOGY		Colour rendering index		80-89		Protection class (IP)	IP54
Max. mounting height	6,00 m	With illuminant		Yes, STEINEL LED system		Protection class	I
Sensor technology	passive infrared	Illuminant		LED cannot be replaced		Ambient temperature	-20 – 40 °C
With motion detector	Yes	LED cooling system		Passive Thermo Control		Housing material	Aluminium
Detection angle	240 °	Luminous flux		2400 lm		Cover material	Plastic, transparent
Opening angle	180 °					SCOPE OF DELIVERY & WARRANTY	
Sneak-under protection	Yes					Manufacturer warranty	5 years

XLED PRO Wide eNet - schwarz

Product code **4007841010249**

Illustrations

MOUNTING HEIGHT



XLED PRO Wide eNet - schwarz

Product code 4007841010249

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841032821	eNet Funk Handsender 2-fach	
 4007841032838	eNet Schaltaktor	

ORDERING INFORMATION

Art.-Nr.

4007841010249

Typ

XLED PRO Wide eNet - schwarz

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss