

iFux CityStreet4 28W DN10 3K

IFUX CITYSTREET 4

neva
lux

Product code **221192**

- Pole mounted luminaire for universal outdoor use
- High-quality, noble processing with glare-free illumination
- Designed for the lighting of urban, street and pedestrian areas
- Also available as intelligent Connect luminaire with built-in, networkable sensor technology
- 5 years warranty

neva
lux

458 x 240 x 100 mm



iFux CityStreet4 28W DN10 3K

Product code 221192

IFUX CITYSTREET 4

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		HOUSING & MATERIAL	
Variant	Narrow beam DN10, 28W	Colour temperature	3000 K	Impact resistance	IK09
DIMENSIONS		Colour rendering index	70-79	Protection class (IP)	IP66
Dimensions L x W x H	458 x 240 x 100 mm	With illuminant	Yes, LED-System	Protection class	II
Suitable for pole-top diameter	48...76 mm	Luminous flux	3976 lm	Ambient temperature	-30...55 °C
ELECTRICAL		Beam angle	Narrow	Housing material	Aluminium
Mains connection	90...264 VAC / 47 – 63 Hz	Luminaire luminous efficacy	142 lm/W	Cover material	Clear glass
Power	28 W	LIFETIME		Mounting type	Column side-entry
Power factor	0.92	LED lifespan (25 °C)	100000 h	Colour	Anthracite
SENSOR TECHNOLOGY		SETTINGS		SCOPE OF DELIVERY & WARRANTY	
With motion detector	No	DALI dimming	Yes	Manufacturer warranty	5 years
With light sensor	No	With program-controlled lighting control	No	With connection cable	Yes
CONNECTIVITY				CERTIFICATES & EPREL	
With radio network control	No			EPREL energy efficiency class	A++, A+, A (LED)

iFux CityStreet4 28W DN10 3K

IFUX CITYSTREET 4

Product code **221192**

Accessories

ORDERING INFORMATION	
Art.-Nr.	221192
Typ	iFux CityStreet4 28W DN10 3K
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	