

IS 300 weiss

neva
lux

Product code **4007841602215**

- Wireless interconnection
- Including corner wall mount
- UV-resistant plastic

neva
lux

85 x 60 x 95 mm



IS 300 weiss

Product code **4007841602215**

Technical Data

IDENTIFICATION			
Variant	white	Segment-by-segment masking	Yes
Version	Motion detectors	Electronic scalability	No
DIMENSIONS		Mechanical scalability	No
Dimensions L x W x H	85 x 60 x 95 mm	Radial range	r = 3 m (24 m²)
ELECTRICAL		Tangential range	r = 12 m (377 m²)
Mains connection	230 – 240 V , 50 / 50 Hz	Switching zones	456 switching zones
Switching output 1 resistive	2000 W	Optimal mounting height	2 m
SENSOR TECHNOLOGY		CONNECTIVITY	
Sensor technology	passive infrared	Networking	Yes
Detection angle	300 °	LIGHTING TECHNOLOGY	
Opening angle	180 °	Constant light regulation	No
Sneak-under protection	Yes	SETTINGS	
		Twilight setting	2 – 2000 lx
		Time setting	10 sec – 15 min
		Base light function	No
		With remote control	No
		Twilight setting teach	No
		HOUSING & MATERIAL	
		Protection class (IP)	IP54
		Ambient temperature	-20 – 50 °C
		Mounting location	corner wall
		Application location	Indoors Outdoors
		Mounting type	Surface wiring
		Material	Plastic
		Colour	white
		RAL colour	9010
		SCOPE OF DELIVERY & WARRANTY	
		Manufacturer warranty	5 years

IS 300 weiss

Product code **4007841602215**

Illustrations

MOUNTING HEIGHT



IS 300 weiss

Product code 4007841602215

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841630218	Eckwandhalter 01 weiss	Corner adapter
 4007841630119	Eckwandhalter 01 schwarz	Corner adapter

ORDERING INFORMATION

Art.-Nr.

4007841602215

Typ

IS 300 weiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss