

IS 3360 LiveLink - Unterputz rund

neva
lux

Product code 4007841049393

E-Nr. 535955307

neva
lux

124 x 78 mm



IS 3360 LiveLink - Unterputz rund

Product code **4007841049393**

E-Nr. **535955307**

Technical Data

IDENTIFICATION					
Variant	LiveLink - concealed installation, round	Mechanical scalability	No	With remote control	No
Version	Motion detectors	Radial range	Ø 8 m (50 m²)	Twilight setting teach	Yes
Model	LiveLink	Tangential range	Ø 40 m (1257 m²)	HOUSING & MATERIAL	
DIMENSIONS		Switching zones	1416 switching zones	Protection class (IP)	IP20
Dimensions Ø × H	124 x 78 mm	Mounting height	2,50 – 4,00 m	Ambient temperature	-20 – 50 °C
ELECTRICAL		Presence range	Ø 3 m (7 m²)	Mounting location	ceiling
Mains connection	230 V, 50 / 60 Hz	Optimal mounting height	2,8 m	Application location	Indoors Outdoors
Supply voltage detail	DALI bus	CONNECTIVITY		Mounting type	Concealed wiring
Livelihood values	Light level, Motion detection	Networking	Yes	Material	Plastic
SENSOR TECHNOLOGY		Number of DALI participants	3	Colour	white
Sensor technology	passive infrared	LIGHTING TECHNOLOGY		RAL colour	9010
Detection angle	360 °	Constant light regulation	No	SCOPE OF DELIVERY & WARRANTY	
Opening angle	180 °	SETTINGS		Manufacturer warranty	5 years
Sneak-under protection	Yes	Twilight setting	2 – 1000 lx	OTHER	
Segment-by-segment masking	Yes	Time setting	5 sec – 15 min	Application, location, room	sports hall, side room, stairwell, wc, washroom, multi-storey car park, underground car park, warehouse, equipment room
Electronic scalability	No	Base light function	No		
		Settings via	LiveLink app		

IS 3360 LiveLink - Unterputz rund

Product code **4007841049393**
E-Nr. **535955307**

Illustrations

MOUNTING HEIGHT

2,50 – 4,00 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

IS 3360 LiveLink - Unterputz rund

Product code **4007841049393**E-Nr. **535955307**

Accessories

ORDERING INFORMATION

Art.-Nr. 4007841049393

E-Number 535955307

Typ **IS 3360 LiveLink - Unterputz rund****neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss